

Standard Gage Pin

Style "C" Tapered Locating Pin

Dim. Tol. Nom.Dia.	Y +/-0.1 -0.50		Dim. Tol. Nom.Dia.	Y +/-0.1 -0.50	
Nom. Dia.	Assy Call Out	V Bushing	Nom. Dia.	Assy Call Out	V Bushing
04.00	N04.00C 03.50	P16-10-3MM	26.00	N26.00C 25.50	P48-16-12MM
04.50	N04.50C 04.00		26.50	N26.50C 26.00	
05.00	N05.00C 04.50		27.00	N27.00C 26.50	
05.50	N05.50C 05.00		27.50	N27.50C 27.00	
06.00	N06.00C 05.50		28.00	N28.00C 27.50	
06.50	N06.50C 06.00		28.50	N28.50C 28.00	
07.00	N07.00C 06.50		29.00	N29.00C 28.50	
07.50	N07.50C 07.00		29.50	N29.50C 29.00	
08.00	N08.00C 07.50		30.00	N30.00C 29.50	
08.50	N08.50C 08.00		30.50	N30.50C 30.00	
09.00	N09.00C 08.50	P20-12-4MM	31.00	N31.00C 30.50	
09.50	N09.50C 09.00		31.50	N31.50C 31.00	
10.00	N10.00C 09.50		32.00	N32.00C 31.50	
10.50	N10.50C 10.00		32.50	N32.50C 32.00	
11.00	N11.00C 10.50	P28-12-6MM	33.00	N33.00C 32.50	
11.50	N11.50C 11.00		33.50	N33.50C 33.00	
12.00	N12.00C 11.50		34.00	N34.00C 33.50	
12.50	N12.50C 12.00		34.50	N34.50C 34.00	
13.00	N13.00C 12.50		35.00	N35.00C 34.50	
13.50	N13.50C 13.00		35.50	N35.50C 35.00	
14.00	N14.00C 13.50		36.00	N36.00C 35.50	
14.50	N14.50C 14.00		36.50	N36.50C 36.00	
15.00	N15.00C 14.50	P48-16-10MM	37.00	N37.00C 36.50	
15.50	N15.50C 15.00		37.50	N37.50C 37.00	
16.00	N16.00C 15.50		38.00	N38.00C 37.50	
16.50	N16.50C 16.00		38.50	N38.50C 38.00	
			39.00	N39.00C 38.50	
17.00	N17.00C 16.50	P48-16-12MM	39.50	N39.50C 39.00	
17.50	N17.50C 17.00		40.00	N40.00C 39.50	
18.00	N18.00C 17.50		40.50	N40.50C 40.00	
18.50	N18.50C 18.00		41.00	N41.00C 40.50	
19.00	N19.00C 18.50		41.50	N41.50C 41.00	
19.50	N19.50C 19.00		42.00	N42.00C 41.50	
20.00	N20.00C 19.50		42.50	N42.50C 42.00	
20.50	N20.50C 20.00		43.00	N43.00C 42.50	
21.00	N21.00C 20.50		43.50	N43.50C 43.00	
21.50	N21.50C 21.00		44.00	N44.00C 43.50	
22.00	N22.00C 21.50		44.50	N44.50C 44.00	
22.50	N22.50C 22.00				
23.00	N23.00C 22.50				
23.50	N23.50C 23.00				
24.00	N24.00C 23.50				
24.50	N24.50C 24.00				
25.00	N25.00C 24.50				
25.50	N25.50C 25.00				